

Specification: "Compact" ALUMINIUM SECTIONAL OVERHEAD DOOR

version: 102.0 date: 01-07-2000

- 1 Manufacturer: Rolflex Nederland B.V. of Ulft.
- 2 Impermeability (NEN 2778+w97): up to 600 Pa.
- 3 Strength and rigidity (NEN 6702+w97): up to 600 Pa.
- 4 Type: Compact sectional door.
NOTE: All the door sections fold together above the doorway.
- 5 Dimensions: - width (mm):
- height (mm):
- 6 Door sections: insulated stucco sandwich panels.
- 7 height (mm): 610.
- 8 thickness (mm): 40.
- 9 insulating material: hard polystyrene core.
- 10 - internal and external lining: aluminium stucco panels, total thickness 0.8 mm
- 11 Surface treatment: anodised, silicon polyester
Option: powder coated rails.
Standard colours (RAL):
 - 3002 Carmine red
 - 5010 Ocean blue
 - 5017 Traffic blue
 - 6005 Moss green
 - 7016 Anthracite grey
 - 7032 Pebble grey
 - 9002 Grey white
 - 9006 White aluminium.- colour of the outside (RAL)
- 12 Glazing: acrylate, double-glazed full-vision panels.
\Glazing: acrylate, double-glazed snap-in windows.
- 13 Ventilation panel (w x h) (mm): 450 x 90.
\Ventilation panel.....
- 14 Wicket door (w x h) (mm): 875 x 2200 approx.
- 15 Operation: #
\electrical, tubular motor 230 V.
\electrical, slip-fit motor 400 V.
\electrical, high-speed motor 400 V.
\electrical, top-mounted motor.... \with hand chain hoist.
NOTE: A top-mounted motor is required if space at the side is limited.
- 16 \- impulse transmitter: dead man's system.
\- impulse transmitter: switch.
\- impulse transmitter: pull switch. \- impulse transmitter....
- 17 \Accessories:
- 18 \- door furniture.....
- 19 \- hinges: corrosion-resistant steel.
- 20 \- door fittings: hot-dip galvanized. \- door fittings....
- 21 \- seals: rubber.
- 22 \- cable break protection.
- 23 \- fall protection.
- 24 \- anti-lift protection.
- 25 \- spring-mounted floor consoles.
- 26 \- object detection system.
- 27 \- fixings.....
- 28 \-.....