



COMPACT CRANE TRACK DOORS

More space, more comfort, more efficiency



Table of contents

Compact crane track doors	4
Maximize space	5
Comfortable working environment	6
Maintenance	7
Renovation	8
Safety	9
Installation & Service	10
Reference projects	11
Technical specifications	16
More info & Contact	17



Compact CRANE TRACK DOORS from Rolflex



*25+ years of
satisfied customers*

Maximum height, minimum hindrance.

In halls with crane tracks, optimal use of the available space is essential. Standard door solutions are often not an ideal solution here. They limit the available working height, offer poor insulation or do not let in any light.

The Compact door offers the best of both worlds: a minimal installation depth and a well-insulated, translucent solution. This allows you to use your crane track and your space optimally, without compromising on comfort or appearance.



*Worldwide
delivery*



*Custom made in our
own factory in the
Netherlands*





MAXIMUM UTILISATION OF SPACE

- Install the crane track directly above your door without compromising door height or working height.
- The crane track can be attached to the facade (construction), there is no need to remove the track from the wall.
- Option: The door can also be mounted completely outside the building for optimum space saving.



A COMFORTABLE, LIGHT WORKING ENVIRONMENT

- Windows or glass panels for more natural light in your workshop
- Compact doors are insulated. This keeps your hall frost-free.



LOW MAINTENANCE, COST SAVING

- No torsion springs, meaning fewer moving parts and significantly lower maintenance costs compared to standard sectional doors.
- Durable design, tested to over 100,000 cycles.
- Over 30 years of innovation: this generation of Compact doors is better than ever.

PERFECT FOR RENOVATION

- Thanks to its compact size, you can easily replace old roller or sliding doors. Without complicated renovations.
- A facelift for your building in 1 day!
- Available with integrated wicket doors for easy access.



Compact & SAFE



Fall protection

Prevents damage or injury if the steel cable breaks.



Daylight protection

Compact doors with automatic closing are always equipped with a light curtain to prevent anything or anyone from becoming trapped under the closing door.



Automatic locking

The automatic lock ensures that the door is always locked and cannot be opened from outside without permission.



Slack cable protection

Prevents damage when the cable loses tension

All Compact doors comply with European Safety Standard **EN 12604** and **EN 12453**, **NEN 13 241-1** and are **CE certified**.





Installation & **SERVICE**

Satisfied customers, trouble-free lifespan.

You may not realize it right away, but every business door is an essential part of your business. A non-functioning door can have a major impact on your business.

A Compact door will last for a long time. Professional installation and service are important contributors to a successful and trouble-free lifespan.

Reference **PROJECTS**



Ter Linden Transport

Three Compact doors adorn the hall of Ter Linden. They were able to have a higher door installed by the Compact door, which also allows them to move larger goods easily.



CGT Carugate Milan

In this renovation project, the Compact doors ensured that neither the crane track nor the windows above the door were blocked. The hall is now lighter and better insulated than before.



Gloucester and Catterick Military Base

In this base, the crane track moves freely through the entire space thanks to the Compact doors.



DEMI Container services

At this container company, the Compact door ensures a smooth and efficient work process.

Technical SPECIFICATIONS

Min/Max dimensions

Maximum dimensions for a Compact door are 7000 mm wide and 7960 mm high. In doors of 7 meters or wider, maximum 2 glass panels.

Colors and materials

Panels are available in 10 standard colours and optionally in all RAL colours. Glass panels or windows possible.

Sealing on all sides

The door opening is sealed on all four sides and between panels with rubber seals.

Dimensions of the headroom and depth

Depth of the door package: 730 mm

The **additional space** (above the door opening) required depends on the height of the door:

< 3080mm	: 420mm
3081- 4300mm	: 520mm
4300 - 5520mm	: 630mm
5521 - 6740mm	: 770mm
6741 - 7960mm	: 890mm

All Compact doors comply with European safety standards **EN 12604** and **EN 12453**, **NEN 13 241-1** and **CE certified**.



Option: Mounting on the outside of the building for additional space saving

Download our comprehensive product information booklet for all options.

rolflex.com/en/downloads



More info & **CONTACT**

To ask?

Please feel free to contact us if you have any questions or visit our website for frequently asked questions, downloads and reference projects.

Design your own Compact door

Discover all options, receive drawings and quotes from your local dealer using our free online Compact door configurator:

configurator.rolflex.com



Rolflex Nederland BV
Nijverheidsweg 23
7081 AE Uift
Netherlands

+31 (0)315 695959
sales@rolflex.com

Rolflex.com